Roche[®] LightCycler[®] 480 real-time PCR run setup instructions for qBiomarker Somatic Mutation PCR Arrays

Important points before starting

- Please read the handbook supplied with the qBiomarker Somatic Mutation PCR Array, paying careful attention to the "Safety Information" and "Important Notes" sections, before beginning this procedure.
- Make sure the real-time PCR instrument is working properly. Refer to the manufacturer's Installation and Maintenance manual if needed.
- Make sure the correct thermal block cycler (384-well block format for G plate or 96-well for F plate) is in place.
- Turn on the LightCycler 480 instrument; the main switch is located at the back of the instrument. Turn on the computer linked to the instrument and log on to Windows[®] XP.

Procedure

Creation of PCR protocol template

- 1. Start LightCycler 480 software 1.5.0 SP3 (version 1.5.0.39).
- Enter "Username" and "Password" when the "Login" dialog box appears and click the Dotton to proceed with the login. The "Overview" window will appear.
- 3. Wait for the initiation of the instrument to finish and the two status LEDs on the front of the instrument to become stable. The left LED should become a steady green while the right LED should be a steady orange.
- 4. In the "Overview" window (Figure 1), click the "New Experiment" button on the right-hand side of the window to launch the "Run" module.






Figure 1. "Overview" window.

- 5. In the "Setup" area at the top of the "Run Protocol" tab (Figure 2), specify the following setup parameters:
 - "Detection Format": "Monocolor Hydrolysis probe" (click on "Customize" to make sure active filter combination is "FAM(483-533)")
 - "Block Type": should show the correct block format (384 or 96)
 - "Plate ID": (Optional)
 - "Reaction Volume": "10 μ l" for G plate or "25 μ l" for F plate

	480_1357	/ Standby	(no MWP)					Databa	ise: My Cempu	ter (Traceable)		
N	ew Experi	ment					•	User:	System Ad	min		
		Ren	Protocol			Data			Run N	otes		
Dete		mat flows	Color H	iydrolysis Fro	be	Custemize	Block Size	304	Plate ID	Reactio	on Volume 10	췬
Cole	or Comp II				Lot No	-		Test ID	-			_
	16 Low	100				Programs				0.5865		
		am Name								Cycles	Analysis Mod	e
Ð		activati	on							1 Non		-
	Progr	6.01								1 Non	e.	
Θ												
C.	1											
\mathbf{r}												
	1					(A) A)						
1	Ta	inget (*Q	A-1	quisition Mode	Hold (hhommosa)	Program Temperature Ramp Rate (*C/s)		lase 10	Sec Target (*C)	Stee Size (1)	Step Delay (a selasti
-	(¹⁰	ager (Q	PAC	rdemaco moce	inter (nn.mm.zel	Hamp Hater (Crs)	Acquisitions	(per C)	Sec Larger (C)	Step Stre (C)	Steb neral is	cyciesi
\odot	¥ 95		None		. 00:10:00	04.8				0	0	4
Θ												
						(A						
	ю.					Overview						-
10												_]
10	× 1											-
10	ю Г											-
10				_								-
10												-
Temperature (C)												-
Temperature (C)	10 10 10 10											-
Temperature (C)												
Temperature (C)	10 10 10 10						4)		_	_	10	215

Figure 2. Initial "Run Protocol" window.

- 6. In the "Programs" section, click the 💽 button twice to add two more program lines.
- 7. Click to change the "Program Name" of the first program to "Heat Activation". Leave the number of "Cycles" at "1" and leave the "Analysis Mode" as "None". In the "Program Temperature Targets" section, enter the values for the following parameters (see Figure 3):

Target (°C)	Acquisition mode	Hold (hh:mm:ss)	Ramp rate (°C/s)	Acquisition (per °C)	Sec target (°C)	Step size (°C)	Step delay (cycles)
95	None	00:10:00	4.8*		0	0	0

New	0_1357 / Standby Experiment	(no sawr)			·	User:	sse: My Cempul System Ad		
		Pretocol		Data			Run N	otes	
Detecti		o Color Hydrolysis Fro	ibe	Customize	Block Size	204	Plate ID	Reactio	n Volume 🔟 🚖
Contraction of	Comp ID		Lot No			Test ID	and the second second		
				Programs			14		
	Program Name			0.000				Cycles	Analysis Mode
•	Heat activati	on						1 None	
	Program							1 None	
Θ									
0									
m				Program Temperatur					
	Target (*Q	Acquisition Mode	Hold (hhommoss)	Ramp Rate ("C/s)	Acquisitions	s (per "C)	Sec Target (*Q)	Step Size (*C)	Step Delay (cycles)
Đ,	95	None		04.0			0	0	0
Θ									
				Overview					
100									
100 00 00 00 00 00 00 00 00 00 00 00 00	50								1015

Figure 3. Setup for the first program — "Heat Activation."

8. Click to change the "Program Name" of the 2nd program to "PCR Cycling". Change the number of "Cycles" to "45"[†] and change the "Analysis Mode" to "Quantification". In the "Temperature Targets" section, click the button twice to add two more temperature target lines. Enter the values for the following parameters (Figure 4):

Target (°C)	Acquisition mode	Hold (hh:mm:ss)	Ramp rate (°C/s)	Acquisition (per °C)	Sec target (°C)	Step size (°C)	Step delay (cycles)
95	None	00:00:15	1.0		0	0	0
60	None	00:01:00	1.0		0	0	0
70	Single	00:00:30	1.0		0	0	0

[†] The PCR is run for extra five cycles (i.e. 45 cycles) rather than the typical 40 cycles, as this will allow the use of the Second Derivative Maximum method available with the LightCycler 480 software for data analysis. See Data Analysis section for further details.

	LC48	0_1357 / Standby	(no MWP)					Database	My Cempu	ter (Traceable)		
	New	Experiment					-	User:	System Ad	min		
		Ren	Protocol			Data			Ren N	otes	1	
	Setup		o Color Hydrol	ante Breit		Customize	Bleck Size 204		late ID	Beactio	n Volume 10	췴
		Comp ID	e corer allarer	Para Prob	Lot No	(commute)	200000000000	Test ID	400 10 1	Teecco	in voidine [io	-
Ľ	Johor C	comp to j			cornol	100000000000000000000000000000000000000		res in 1				
1	~	Program Name				Programs				Cycles	Analysis Mode	_
G	_	Heat activati	ion							1 None		
0	Ð	Program								1 Nose		
E	E											
\sim	-											
0	~											
0						Program Temperature	Tarnets					-
12		Target (*Q	Acquisitio	n Mode	Hold (hhommosa)	Ramp Rate ("C/s)	Acquisitions (per	'Q Se	c Target (°C)	Step Size (*C)	Step Delay (c	yclesi
G	Ð,	1012200000		1999455		and the second s	General Montes			and the second s		200
		95	None		• 00:10:00	<u>4.8</u>	31	0	0	• •	0	- 2
IC	Ð											
01	1											
0	\sim											
						(A						
						Overview						
	100											
	100 90	-										
	90											
ture (C)	90											
time (C)	90 7 00 70											
	90 7 00 70											
time (C)	90 7 00 70											
time (C)	90 70 70 60 50											
time (C)	90 7 80 70 60 50 40	0									10	15
time (C)	90 70 60 90 40 30	0				Enternated Time (formerce	6).				10	15

Figure 4. Setup of the second program — "PCR Cycling."

9. Click the down arrow button () right next to the "Apply Template" button on the lower left corner of the screen; select the "Save As Template" button (Figure 6) to save the run template under the filename "qBiomarker_Mutation_PCR_Array_384_LC" if using the 384-well format or "qBiomarker_Mutation_PCR_Array_96_LC" if using the 96-well format.

and the second se	Run Protocol		Data		Run N	otes	
Setup Detection Format	STBR Green I		Customize	Block Size 304	Plate ID	Reaction	Volume 10
Color Comp ID		Lot No		Test	10		
A			Programs				
riopam							Analysis Mode
Beat Act PCR Cycl						1 None 45 Quan	tification
A Meit Cur							ing Curves
V							
			Line and				
Tarne			Program Temperature				
	(C) Acquisition Mod	e Hold (hhommoss)	Ramp Rate ("Ch)	Acquisitions (per *C)	Sec Target (*C)	Step Size (C)	Step Delay (cycles
•	None	00100115	\$2.5 Q		6		
A 95	Continuous			20			
100			Tenplate	MAA_Tangdates plates tee Templates plates			7
Tamparátae (%)							

Figure 5. Saving the "Run Template" file.

Real-time PCR detection

To load the PCR array plate and start the run:

- 10. Prepare the PCR array following the *qBiomarker* Somatic Mutation PCR Array Handbook.
- Make sure the correct thermal block (384-well block format for G plate or 96-well for F plate) is in place.
- 12. If the instrument is not on, turn it on using the main switch at the back of the instrument. Turn on the computer linked to the instrument and log on to Windows XP.
- 13. Start LightCycler 480 software (version 1.5.0.39).
- 14. Enter "Username" and "Password" when the "Login" dialog box pops up and click the State button to proceed with the login. The "Overview" window will appear.
- 15. Wait for the two status LEDs on the front of the instrument to become stable. The left LED should become a steady green while the right LED should be a steady orange.
- Press the ←→ open/close button on the front of the instrument (located next to the instrument status LEDs). The plate loading arm will slide out of the right side of the instrument. Place the PCR array plate into the frame of the loading arm with the flat

Roche LightCycler 480 real-time PCR run setup instructions for qBiomarker Somatic Mutation PCR Arrays

edge of the array closest to the instrument and the edge with a beveled corner pointing away from the instrument.

- Press the ←→ open/close button again to retract the loading arm. Wait for both of the status LEDs to turn steady green.
- 18. In the "Overview" window, click the "New Experiment" button on the right-hand side of the screen.
- In the "Run Protocol" tab, click the "Apply Template" button on the lower left corner of the screen. Select and double-click to open the appropriate previously saved "qBiomarker_Mutation_PCR_Array_384_LC" or "rePiermarker_Mutation_PCR_Array_84_LC"

"qBiomarker_Mutation_PCR_Array_96_LC" run template file.

20. Press the "Start Run" button on the lower right corner of the screen to initiate the run. When prompted, save the file under a new filename after which the run will begin.

Data analysis

- 21. In the "Navigator" window, find and open the run file to be analyzed.
 - For data analysis using the LightCycler 480, we highly recommend the use of the Second Derivative Maximum analysis method available in this software. This is an algorithm based on the kinetics of a PCR reaction. This method identifies the crossing point (Cp) of a PCR reaction as the point where the reaction's fluorescence reaches the maximum of the second derivative of the amplification curve, which corresponds to the point where the acceleration of the fluorescence signal is at its maximum. Hence, this crossing point should always be located in the middle of the log-linear portion of the PCR amplification plot. The advantage of this analysis method is that it requires little user input and produces consistent results.
- 22. Obtaining the Crossing Point (Cp) Cycle values: Once the selected run file is open, click the "Analysis button" on the left-hand side of the window. In the "Create new analysis" list, double-click to select "Abs Quant/2nd Derivative Max". In the "Create new analysis" window that opens, make sure the "Analysis Type" is "Abs Quant/2nd Derivative Max". Click 🐼 to confirm the selection.
- 23. The "Analysis Window" with the amplification curves will appear. To proceed, click the down arrow button () on the lower right corner of the screen to set the analysis to "High Confidence." Next click the "Calculate" button to generate Cp values. The calculation may take a few minutes.

24. Once the Cp values are generated, move the mouse over to the "Samples" window and click to highlight the Samples result table. Right click the "Export" button to export the data. A "Save table data" dialog box will appear (Figure 10). Enter a filename to save the data as a text file. Then click the 🗐 button on the right panel to save the Second Derivative Maximum analysis and the Cp values as part of the run file.

The qBiomarker Somatic Mutation PCR Arrays are intended for molecular biology applications. These products are not intended for the diagnosis, prevention, or treatment of a disease.

For up-to-date licensing and product-specific disclaimers, see the respective QIAGEN kit handbook or user manual. QIAGEN handbooks can be requested from QIAGEN Technical Service or your local QIAGEN distributor. Selected handbooks can be downloaded from <u>www.qiagen.com/literature</u>. Safety data sheets (SDS) for any QIAGEN product can be downloaded from <u>www.qiagen.com/safety</u>.

Trademarks: QIAGEN® (QIAGEN Group); Roche®, LightCycler® (Roche); Windows® (Microsoft Corporation). Dec-12 © 2012 QIAGEN, all rights reserved.

www.qiagen.com Australia = 1-800-243-800 Austria = 0800/281010 Belgium = 0800-79612 Canada = 800-572-9613 China = 021-51345678 Denmark = 80-885945 Finland = 0800-914416 France = 01-60-920-930 Germany = 02103-29-12000 Hong Kong = 800 933 965 Ireland = 1800 555 049 Italy = 800 787980 Japan = 03-6890-7300 Korea (South) = 1544 7145 Luxembourg = 8002 2076 The Netherlands = 0800 0229592 Norway = 800-18859 Singapore = 65-67775366 Spain = 91-630-7050 Sweden = 020-790282 Switzerland = 055-254-22-11 UK = 01293-422-911 USA = 800-426-8157



Sample & Assay Technologies